

CPCBC4001A

APPLY BUILDING CODES AND STANDARDS TO THE CONSTRUCTION PROCESS FOR LOW RISE BUILDING PROJECTS

ASSESSMENT SUMMARY

The assessment activities for *CPCBC4001A Apply building codes and standards to the construction process for low rise building projects* cover all aspects of the unit of competency required. To demonstrate competence in this unit, a participant must undertake all tasks and complete them satisfactorily and consistently. For Apprentices and Trainees, this includes employer completion of the Employer Record Book (ERB).


Participants must read all the information given before starting any assessment task. The assessment tasks are intended to be equitable, fair and flexible. If a participant has any questions or requires alternative arrangements to be made such requests should be directed to their Trainer/Assessor, who should note such arrangements in the 'Assessor Comments' on the affected assessment. If a participant feels they are not yet ready to be assessed, they should discuss their options with their Trainer/Assessor.

To satisfactorily complete the assessment, the participant is required to answer all questions correctly and demonstrate their skills to industry standards. If a participant does not answer some questions or perform some tasks, they will be deemed 'Not Satisfactory' for the task and 'Not Yet Competent' for the unit of competency. The Trainer/Assessor is able to provide the participant with additional information on interpreting the assessment outcomes and provide guidance on the participant's options. Should a participant still be deemed 'Not Satisfactory' they will have the opportunity to undertake a supplementary assessment or appeal the result.

By signing the cover page for each assessment item, the participant acknowledges they understand the assessment instructions and requirements and consent to being assessed. The participant also verifies and assures the RTO that the work submitted is their own work.

Participant Name	YANZHONG ZHU
------------------	--------------

Task	Assessment Results	
Theory Exam	☐ Satisfactory	☐ Not Yet Satisfactory
Practical Assessment	☒ Satisfactory	☐ Not Yet Satisfactory
Outcome for Unit of Competency	☐ Competent	☐ Not Yet Competent

Assessor Name	Shane Lawson
Assessor Signature	
Unit Competence Determination Date	16 10 2020

CPCCBC4001A


APPLY BUILDING CODES AND STANDARDS TO THE CONSTRUCTION PROCESS FOR LOW RISE BUILDING PROJECTS

THEORY EXAM INSTRUCTIONS

- This exam will occur under standard assessment conditions.
 - An oral examination may be allowed under certain circumstances, whereby the Participant's answers will be documented by a party other than the Participant. This must be acknowledged in writing (e.g. FT001 and Assessor Comments)
- Participants must provide enough detail in their responses to demonstrate their knowledge and skills.
- Please fill in the details below, providing your name, signature and date of assessment.
 - Your signature acknowledges that this is your own work.
- Assessors are to complete marking in pen of a different colour to the Participant.
- If a Participant initially answers a question incorrectly but modifies their response, they must follow the instructions below:
 - If a Participant changes their response in writing, they must put their initials next to the written change.
 - If a Participant changes their response verbally, this must be noted on the exam paper by the assessor.

Participant name YANZHONG ZHU

Participant signature



Date 8/09/2020

Assessor name Shane Lawson

Assessor signature



Date Click here to enter a date. 16 10 2020

Number of questions	Number of questions answered correctly	Task outcome (Tick)	
		Satisfactory	Not Yet Satisfactory
38	35	☐	☐

ASSESSOR COMMENTS
Q1 one to many answers Q15 half right if you test them and some dont work what would you do? Q33 check class Good work

- Q1. A Performance Solution must abide by which of the following?**
Tick all that apply.

Answer	Choice	Possible Answers	☐
	☒	Be assessed according to one or more of the Assessment Methods	
	☒	Go beyond the requirements of Deemed-to-Satisfy Provisions	
	☒	Comply with the Performance Requirements	☒

- Q2. True or False (Tick your response): The Performance Requirements of the National Construction Code can be achieved by using a Performance Solution, a Deemed-to-Satisfy Solution, or a combination of both.**

Answer	☒	True	☒
	☐	False	

- Q3. True or False (Tick your response): The term 'Performance Solution' in the NCC was formerly known as 'Alternative Solution'.**

Answer	☒	True	☒
	☐	False	

- Q4. Where a Performance Solution has been proposed, which of the following documentation should be prepared and retained?**
Tick all that apply.

Answer	Choice	Possible Answers	☒
	☒	Details of the relevant Performance Requirements	
	☒	Assessment Methods used to establish compliance with the relevant Performance requirements	
	☒	Details of any Expert Judgement relied upon	
	☒	Details of any tests or calculations used to determine compliance with the Performance Requirements	
	☒	Details of any Standards or other information which were relied upon	

Q5. True or False (Tick your response): Where a Deemed-to-Satisfy solution has been proposed, all relevant plans/specifications should be retained.

Answer

☒	True
☐	False



Q6. Identify the Volume and Parts of the NCC that outline the Assessment Methods used to determine whether a Performance Solution or a Deemed-to-Satisfy Solution complies with the Performance Requirements for Classes 1 and 10, and Classes 2 to 9.

Answer

Classes 1 and 10	Classes 2 to 9
Volume two, Part A6	Volume one, Part A6



Q7. Identify the Australian Standard that relates to artificial lighting needed for safe movement, as noted in the NCC.

Answer

Artificial lighting must be installed to provide an *illuminance* of not less than 20 lux appropriate to the function or use of the building to enable safe movement by occupants. as 1680



Q8. Identify the Volume and Parts of the NCC that outline the requirements for artificial lighting needed for safe movement for Classes 1 and 10, and Classes 2 to 9.

Answer

Classes 1 and 10	Classes 2 to 9
Volume two, 3.12.5.5	Volume one, F4.4



Q9. Fill in the blanks for the statement below, referring to Volume 1 of the NCC with regards to lighting:

Where a Deemed-to-Satisfy Solution is proposed, Performance Requirements

FP4.1 ✓ to FP4.5 ✓ are satisfied by complying with

- (i) F4.1 ✓ to F4.12 ✓; and
- (ii) For a building containing an occupiable outdoor area, Part G6 ✓;
- and
- (iii) for farm buildings and farm sheds, Part H3 ✓.

Where a Performance Solution is proposed, the relevant Performance Requirements must be determined in accordance with A2.2(3) ✓ and A2.4(3) ✓ as applicable.

Answer



Q10. Fill in the blanks for the statement below, referring to Volume 2 of the NCC with regards to light:

Where an alternative light system is proposed as a Performance Requirement to that described in Part 3.8.4 ✓, that proposal must comply with –

- (a) Performance Requirement P2.4.4 ✓; and
- (b) the relevant Performance Requirements determined in accordance with A2.2(3) ✓ and A2.4(3) ✓ as applicable.

Answer



Q11. Identify the Australian Standard that relates to each of the listed types of fire fighting equipment, as noted in the NCC.

Answer

Equipment	Australian Standard
Fire hydrants	AS 2419.1:2017
Fire hose reels	AS/NZS1221
Portable fire extinguishers	AS/NZS 1850:1997 AMDT 1
Smoke alarms	AS 3786



Q12. For each of the listed types of fire fighting equipment, identify whether they are required by the NCC (if so, identify the relevant Part).

Answer	Equipment	Volume 1	Volume 2	
✓	Fire hydrants	Part E1 EP1.3	3.2.8	✓
✓	Fire hose reels	Part E1 EP1.4	N/A	✓
✓	Portable fire extinguishers	Part E1 EP1.4	N/A	✓
✓	Smoke alarms	Specification E2.2a	3.7.5.2, 3.7.5.6	✓

Q13. Identify the applicable Act in your jurisdiction that outlines the requirements for smoke alarm installation in domestic dwellings. Briefly identify the requirements.

Answer	Act name and section(s)	Requirements	
	Building Code of Australia 3.7.2	The owner or lessor of a property must install a working smoke alarm that complies with AS3786. Smoke alarms may be hard wired or battery operated. Lessors cannot enter into tenancy agreements unless smoke alarms are installed within the property. Smoke alarms must comply with the Building Code of Australia. If homes are built after 1994, they must have at least 240V hard-wired alarms. Homes built prior to 1994 can have 9V battery-operated alarms. As per the Building Code of Australia, homes must have at least one smoke alarm per floor, and one in each space between bedrooms.	✓

Q14. Identify the applicable Act in your jurisdiction that outlines the requirements for testing smoke alarms in domestic dwellings. Briefly identify the requirements.

Answer	Act name and section(s)	Requirements	☒
	AS3786-2014	If the smoke alarms are older than 10-years or if they fail to operate when tested they must be replaced. If they are replaced they must be replaced with AS3786-2014 compliant photoelectric smoke alarms and powered by what is currently there (i.e. if they are powered by 240-volt they must be replaced with 240-volt smoke detectors, otherwise they can be powered by 10 year non-removable batteries) All smoke alarms that are required by legislation, when necessary, must be replaced with Australian Standard 3786-2014 compliant smoke alarms.	

Q15. Identify the applicable Act in your jurisdiction that outlines what must occur if smoke alarm in a domestic dwelling does not operate upon testing and when any rectification must occur. Briefly identify the requirements.

Answer	Act name and section(s)	Requirements	☐

✓ Fire and Emergency Services Act 1990 104RD	(1) Within 30 days before the start of a tenancy in a domestic dwelling, the lessor must test each smoke alarm in the dwelling in compliance with section 104RAA(3). Maximum penalty—5 penalty units. (2) During a tenancy in a domestic dwelling, the tenant must test each smoke alarm in the dwelling, in compliance with section 104RAA(3), at least once every 12 months. Maximum penalty—5 penalty units
--	--

Q16. In observation of NCC Volume 2, identify three (3) aspects which should be checked with regards to smoke alarms.

Answer

-Smoke alarms to be connected to consumer mains source

-Location of smoke alarms:

-Interconnection of smoke alarms



**Q17. Must all smoke alarms be interconnected in domestic dwellings?
Explain your response with reference to legislation.**

Answer

3.7.5.2(d) requires that alarms be interconnected to provide a common alarm so that if one alarm in the dwelling activates, the other alarms automatically activate, which will increase the likelihood of sleeping occupants becoming aware of the detection of smoke. Alarms of a Class 1 building need not be interconnected with alarms in another Class 1 building or a *private garage* which does not belong to the Class 1 building.

6.Location of smoke alarms:

When deciding on the position of smoke alarms it is important to remember that they are intended to detect smoke before it reaches the sleeping occupants of a building.

The ensuing alarm is designed to wake the occupants and give them time to evacuate the building.



Q18. Fill in the blanks for the definition of fire compartments, referring to Volume 1 of the NCC:

Fire compartment means –

(a) The total space of a building; or

(b) When referred to in –

- (i) The Performance Requirements – any part of a building separated from the remainder by barriers ✓ to fire such as Walls ✓ and/or floors ✓ having an appropriate resistance to the spread of fire with any openings ✓ adequately protected; or
- (ii) The Deemed-to-Satisfy Provisions – any part of a building separated from the remainder by walls ✓ and/or floors ✓ each having an FRL ✓ not less than that required for a fire wall ✓ for that type of construction and where all opening ✓ in the separating ✓ construction are protected in accordance with the DtS Provisions of the relevant Part.

Answer



Q19. Identify the Volume and Parts of the NCC that outline the requirements for fire compartmentation and separation for Classes 1 and 10, and Classes 2 to 9.

Answer

Classes 1 and 10	Classes 2 to 9
Volume Two, Part 3.7 ✓	Volume One, Part C3 ✓



Q20. Fill in the blanks for the statement below, referring to Volume 1 of the NCC with regards to fire compartmentation and separation:

Where a Deemed-to-Satisfy Solution is proposed, Performance Requirements

- CP1 ✓ to CP9 ✓ are satisfied by complying with
- (i) C1.1 ✓ to C1.14 ✓, C2.1 ✓ to C2.14 ✓
and C3.1 ✓ to C3.17 ✓; and
- (ii) in a building containing an atrium, Part G3 ✓; and
- (iii) for additional requirements for Class 9b buildings, Part H1 ✓; and
- (iv) for farm sheds, Part H3 ✓.

Where a Performance Solution is proposed, the relevant Performance Requirements must be determined in accordance with A2.2(3) ✓ and A2.4(3) ✓ as applicable.

Answer



Q21. Fill in the blanks for the statement below, referring to Volume 2 of the NCC with regards to fire separation:

Where an alternative fire separation design is proposed as a Performance Solution to that described in Part P3.7 ✓ that proposal must comply with Performance Requirement P2.3 ✓; and the relevant Performance Requirements determined in accordance with A2.2(3) ✓ and A2.4(3) ✓ as applicable.

Answer



Q22. Identify the Australian Standard referenced in NCC Volume 1 with regards to compartmentation and separation for electricity supply systems.

Answer AS/NZS 3013



Q23. Identify the Volume and Parts of the NCC that outline the level of fire resistance required for Classes 1 and 10, and Classes 2 to 9.

Answer

Classes 1 and 10	Classes 2 to 9
Volume Two, Schedule 5 ✓	Volume One, Part C1.1 ✓



Q24. In a building's specifications, an FRL is stated as being 90 / 60 / -. If exposed to a standard fire test, how many minutes can you expect this building element to last for the criteria listed below?

Answer

Minutes	Criteria
-	Insulation
60	Integrity
90	Structural adequacy



Q25. Fill in the blanks:

According to NCC Volume 1, an electricity substation located within a building must be separated from any other part of the building by construction having an FRL of no less than 120 / 120 / 120 and have any doorway in that construction protected with a self-closing fire door having an FRL of not less than - / 120 / 30.

Answer



Q26. Fill in the blanks: According to NCC Volume 2, if an electrical wire or cable penetrates a separating wall, the service and building element at the penetration must be identical with a prototype assembly which has been tested and achieve an FRL of not less than - / 60 / 60.

Answer



Q27. Identify the applicable Act in your jurisdiction that outlines the occupier's requirements for maintaining prescribed fire safety installations (e.g. fire doors). Briefly identify the requirements.

Answer

Act name and section(s)	Requirements
Fire and Emergency Services Act 1990 S104D	The occupier of a building must maintain at all times every prescribed fire safety installation to a standard of safety and reliability in the event of fire. It is a defence to a charge made under this Act that an occupier of a building, in contravention of subsection (1), has failed to maintain in the building a prescribed fire safety installation for the defendant For the purposes of this section— Act includes any Act and any proclamation, order in council, regulation, rule, local law or other instrument of subordinate legislation made under any Act, whenever passed or made whether or not it has ceased to exist.



Q28. Identify the applicable Regulation in your jurisdiction that outlines the timeframes in which repair or corrective action must be taken when maintaining prescribed fire safety installations. Briefly identify the requirements.

Answer

Regulation name and section(s)	Requirements
Building Fire Safety Regulation 2008 S31	At any given time, a person is a prescribed person for section 104E of the Fire Service Act if, during the previous 3 months, there have been at least 2 weeks in which the person worked or resided in or visited the building for a total period, in each week, of at least 10 hours.



Q29. NCC Volume 1 outlines that fire doors must be fitted with smoke seals and the assembly must be tested in accordance with Australian Standards. To which classes of building does this specification apply?

Answer Class 5, 6 building



Q30. Do all fire doors require tags? Explain your response with reference to legislation.

Answer Under the Building Act 1975, **all** buildings approved after 1 April 1976 **require tags** to be fitted to the **fire doors**. **Fire doors** that have been replaced after 1 April 1976 also **require tags** to be fitted.



Q31. Match the building classifications and their descriptions by writing the appropriate letter next to each number in the centre column.

Answer	Classification		Answers	Description	
	1	Class 1		A	A non-habitable building or structure.
	2	Class 2		B	A laboratory or a building in which a handicraft or process for the production, assembling, altering, repairing, packing, finishing or cleaning of goods or produce is carried on for trade, sale or gain.
	3	Class 3		C	A residential building other than Class 1 or 2 which is a common place of long term transient living for a number of unrelated persons.
	4	Class 4		D	A dwelling in a building that is Class 5, 6, 7, 8 or 9 if it is the only dwelling in the building.
	5	Class 5		E	May be a single dwelling or a boarding house, guest hose or hostel with a floor area less than 300m ² .
	6	Class 6		F	An office building used for professional or commercial purposes, excluding buildings of Class 6, 7, 8 or 9.
	7	Class 7		G	A shop or other building for the sale of goods by retail or the supply of services direct to the public.
	8	Class 8		H	A building containing 2 or more sole-occupancy units, each being a separate dwelling.
	9	Class 9		I	A building which is a carpark or fore storage/display of goods or produce for sale by wholesale.
	10	Class 10		J	A building of a public nature.



Q32. What class of building would shops, restaurants and cafes belong to?

Answer Class 6



Q33. What class of building would a general medical practitioner's office belong to?

Answer Class 9



- Q34. True or False (Tick your response): At the design stage, it may not be clear who the final tenant will be (or how they will be using their tenancy), so as long as the design meets the minimum requirements of all the classifications, it could be used for any of the purposes.

Answer

☒	True
☐	False



- Q35. Where parts of a building have different purposes, the classification of Class 1 may apply to the whole building if not more than what percentage of the floor area is used for a purpose which is a different classification? Tick your response.

Answer

Choice	Possible Answers
☐	5%
☒	10%
☐	25%
☐	50%



- Q36. The NCC aims to ensure structures appropriately withstand normal forces. Match the terms and definitions below by writing the appropriate letter next to each number in the centre column.

Answer

Term		Answers	Definitions	
1	Bending		A	A force which shortens or crushes.
2	Compression	2 - A	B	A fore which stretches and squashes at the same time.
3	Shear	3 - F	C	A force which tries to pull something apart.
4	Strain	4 - E	D	Intensity of the internally distributed forces that resist a change in the form of a body.
5	Stress	5 - D	E	Physical change in the dimensions of a structure that results from applying a load.
6	Tension	6 - C	F	Created where two opposite forces try to cut, tear or rip something in two.



Q37. True or False (Tick your response): When a beam is loaded, the top is compressed and the bottom is in tension.

Answer

☒	True
☐	False



Q38. True or False (Tick your response): When a cantilever is loaded, the top surface is in tension and the bottom is in compression.

Answer

☒	True
☐	False



CPCCBC4001A

APPLY BUILDING CODES AND STANDARDS TO THE CONSTRUCTION PROCESS FOR LOW RISE BUILDING PROJECTS

PRACTICAL ASSESSMENT INSTRUCTIONS

- The following practical assessment will require the Participant to complete work related activities.
- The Assessor will conduct observations of the Participant's work to determine whether they display sufficient practical skills and knowledge.
- Please fill in the details below – providing your name, signature and date of assessment.
 - The Participant's signature acknowledges that the Assessor provided clear instructions and the Participant understood what was required to complete this assessment.
- The Assessor may substitute a Practical Task with an alternate task of equal value.
 - Alternate tasks must be fully documented by the assessor in the Assessor Comments area.

Participant name YANZHONG ZHU

Participant signature



Date 8/09/2020

Assessor name YING SHE

Assessor signature



Date 8/09/2020

Task	Task outcome (Tick)	
	Satisfactory	Not Yet Satisfactory
Task 1 (Occasion 1)	☒	☐
Task 1 (Occasion 2)	☒	☐

ASSESSOR COMMENTS
Practical evidence provided and 3rd party confirmation

CPCCBC4001A

APPLY BUILDING CODES AND STANDARDS TO THE CONSTRUCTION PROCESS FOR LOW RISE BUILDING PROJECTS

Practical Task 1 (2X)				
Description of task: On two (2) occasions, a suitable observer is to verify the participant's ability to access, interpret and apply relevant building codes and standards. - Occasion 1: Construction classified as Class 1 and 10 construction - Occasion 2: Construction classified in Classes 2 to 9 with a gross floor area not exceeding 2000 square metres, not including Type A or Type B construction The participant is to gather evidence of how they have completed each component of the Practical Task, which is to be submitted with this Practical Assessment sheet. Evidence to be submitted may include: - Documented evidence of determining a compliant solution on a project including: - Correspondence such as letters, emails, and records of other communications - Certifier reports, instructions - Other compliance documentation for a project including: - Council or private certifier inspection reports - Structural inspection certificates - Occupation certificates The observer is to provide detailed comments on the tasks completed by the participant. The assessor is to verify the observer's comments in the Assessor Comments section, and provide the Practical Assessment outcome on the front cover of this document.				
Resources required: Drawings and specifications, National Construction Code, Australian Standards, Relevant legislation.				
Assessment of task				
Name of participant:	YANZHONG ZHU			
Name of observer:	WANG XIN			
Role of observer (Confirm suitability to sign)	Builder			
Email address of observer	Smo.l@live.cn			
Signature of observer:				
Date:	8/09/2020			
When completing the task, did the participant:	Tick if satisfactorily completed. Provide comments if left unticked. <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; text-align: center; border-bottom: 1px solid black;">1st Occasion</td> <td style="width: 50%; text-align: center; border-bottom: 1px solid black;">2nd Occasion</td> </tr> </table>		1 st Occasion	2 nd Occasion
1 st Occasion	2 nd Occasion			
1 Access and interpret codes and standards				
1.A. Identify relevant performance requirements from the National Construction Code that apply to individual projects described as low rise.	☒	☒		
1.B. Determine requirements of relevant National Construction Code deemed-to-satisfy (DTS) provisions.	☒	☒		

1.C. Access and interpret requirements of relevant Australian standards referenced in the National Construction Code.	☒	☒
2 Classify buildings		
1.2A. Determine the nature of building according to its use and arrangement.	☒	☒
1.2B. Apply National Construction Code criteria to determine the defined classification.	☒	☒
1.2C. Identify and interpret National Construction Code requirements for multiple classification.	☒	☒
3 Solutions for compliance		
1.3A. Determine range of criteria to ensure that construction methods comply with National Construction Code performance requirements.	☒	☒
1.3B. In accordance with company policy and procedures, discuss and propose alternative solutions to a design or construction problem that complied with National Construction Code requirements, considering basic design principles and the behaviour of materials and structures under stress, strain, compression, bending or combined actions.	☒	☒
1.3C. Identify and document performance-based solutions in accordance with National Construction Code requirements.	☒	☒
1.3D. Analyse and apply assessment methods referenced in the National Construction Code to determine whether a building solution complied with performance requirements or DTS provision.	☒	☒
1.3E. Identify and complete relevant documentation in accordance with National Construction Code requirements.	☒	☒
1.3F. Effectively communicate using the following methods: - Language/concepts appropriate to cultural differences - Non-verbal communication	☒	☒
4 Fire protection requirements		
1.4A. Identify and apply passive and active fire control elements for low rise buildings, as required by the National Construction Code and other legislation (including WHS requirements).	☒	☒
1.4B. Determine level of fire resistance required for the construction of various low rise buildings.	☒	☒
1.4C. Check existing buildings for compliance with passive and active fire protection requirements, in accordance with National Construction Code requirements.	☒	☒
The Participant's performance was: ☒ Satisfactory ☐ Not Satisfactory		

OBSERVER COMMENTS